

# LASAL 83



**LASAL** is the Air Liquide brand for laser applications

## ● Application

CO2 laser cavity gas

## ● Transport information

### Compressed gas

Proper shipping name

UN Nr

ADR/RID

Compressed gas, N.O.S.

1956

Class 2

Classification Code 1 A



## ● Safety Data Sheet

Access: [www.airliquide.no](http://www.airliquide.no)

## ● Physical information

Relative density, gas . . . . . lighter or similar to air

Colour . . . . . colourless gas

Odor . . . . . none

## ● Properties

Hazards identification: in high concentrations may cause asphyxiation

Flammability range: non flammable

Personal protection: ensure adequate ventilation

## ● Cylinder equipment

Valve fittings :

W 24.32 x 1/14", right, external thread, DIN 10

Shoulder colour: bright green (RAL 6018)



## ● Product Specifications

Components (% Vol. abs)			Impurities (ppm v/v)	Supply mode	Packaging size	Pressure (bar)	Capacity (m³)	Product reference
CO <sub>2</sub>	5 %	±0.25 %	H <sub>2</sub> O (5 bar) ≤ 5	Cylinder	L50	200	10.1	I6680L50R2A001
He	40 %	±2 %	C <sub>n</sub> H <sub>m</sub> ≤ 1					
N <sub>2</sub>	Balance							

## DISCLAIMER

The information contained in this Product Sheet is of a general nature and does not take into account any specific or local condition or regulation and shall neither be considered as recommendations. AIR LIQUIDE assumes no liability or responsibility regarding the information contained in this Product Sheet, the completeness of this document, for the use of the information or consequences of such use, and disclaims all warranties (direct or indirect) of any kind.